

BCE HEM SEALED HEATER™ (< 200 °C) SHIPS IN 2-3 WEEKS								
HEATER PART NUMBER	SheathMaterial	Diameter (mm)	Diameter (inches)	Length (mm)	Length (inches)	WATTAGE	Watt Density in w/in sq.	VOLTAGE
HCSS-3-25	SS	3.18	0.125	25.4	1.0	10	35	120
HCSS-3-26	SS	3.18	0.125	25.4	1.0	15	50	120
HCSS-3-27	SS	3.18	0.125	38.1	1.5	20	40	120
HCSS-3-28	SS	3.18	0.125	38.1	1.5	25	50	120
HCSS-3-29	SS	3.18	0.125	50.8	2.0	35	50	120
HCSS-4-25	SS	4	0.157	25.4	1.0	10	25	120
HCSS-4-26	SS	4	0.157	38.1	1.5	20	35	120
HCSS-4-27	SS	4	0.157	50.8	2.0	35	40	120
HCSS-4.7-25	SS	4.76	0.187	38.1	1.5	30	40	120
HCSS-4.7-26	SS	4.76	0.187	50.8	2	35	35	120
HCSS-4.7-27	SS	4.76	0.187	76.2	3.0	65	40	120
HCSS-4.7-28	SS	4.76	0.187	101.6	4.0	90	40	120
HCSS-4.7-29	SS	4.76	0.187	101.6	4.0	60	25	120
HCSS-4.7-30	SS	4.76	0.187	101.6	4.0	100	45	120
HCSS-6.3-25	SS	6.35	0.250	25.4	1.0	100	250	120
HCSS-6.3-26	SS	6.35	0.250	31.8	1.3	20	25	120
HCSS-6.3-27	SS	6.35	0.250	38.1	1.5	50	50	240
HCSS-6.3-28	SS	6.35	0.250	38.1	1.5	70	85	120
HCSS-6.3-29	SS	6.35	0.250	50.8	2.0	50	35	240
HCSS-6.3-30	SS	6.35	0.250	50.8	2.0	150	125	120
HCSS-6.3-31	SS	6.35	0.250	57.2	2.3	75	50	240
HCSS-6.3-32	SS	6.35	0.250	63.5	2.5	135	85	750
HCSS-6.3-33	SS	6.35	0.250	76.2	3.0	25	11	120
HCSS-6.3-34	SS	6.35	0.250	76.2	3.0	100	45	240
HCSS-6.3-35	SS	6.35	0.250	76.2	3.0	170	90	120
HCSS-6.3-36	SS	6.35	0.250	76.2	3.0	220	115	120
HCSS-12.7-25	SS	12.7	0.500	38.1	1.5	18	12	120
HCSS-12.7-26	SS	12.7	0.500	50.8	2	50	21	120
HCSS-12.7-27	SS	12.7	0.500	50.8	2	200	85	120
HCSS-12.7-28	SS	12.7	0.500	63.5	2.5	150	50	120
HCSS-12.7-29	SS	12.7	0.500	76.2	3	200	50	240
HCSS-12.7-30	SS	12.7	0.500	101.6	4	275	50	240
HCSS-12.7-31	SS	12.7	0.500	127.0	5	120	17	120
HCSS-12.7-32	SS	12.7	0.500	152.4	6	500	70	120
HCSS-12.7-33	SS	12.7	0.500	177.8	7	135	14	120
HCSS-15.9-25	SS	15.9	0.625	50.8	2	65	21	120
HCSS-15.9-26	SS	15.9	0.625	76.2	3	105	21	120
HCSS-15.9-27	SS	15.9	0.625	76.2	3	250	50	240
HCSS-15.9-28	SS	15.9	0.625	101.6	4	145	21	120
HCSS-15.9-29	SS	15.9	0.625	127.0	5	450	50	240
HCSS-15.9-30	SS	15.9	0.625	152.4	6	400	30	120
HCSS-15.9-31	SS	15.9	0.625	152.4	6	540	50	120
HCSS-15.9-32	SS	15.9	0.625	177.8	7	635	50	240
HCSS-15.9-33	SS	15.9	0.625	177.8	7	635	50	120
HCSS-15.9-34	SS	15.9	0.625	177.8	7	160	12	120
HCSS-19.1-25	SS	19.1	0.750	63.5	2.5	230	12	120
HCSS-19.1-26	SS	19.1	0.750	88.9	3.5	350	50	120
HCSS-19.1-27	SS	19.1	0.750	127.0	5	500	50	120
HCSS-19.1-28	SS	19.1	0.750	152.4	6	650	50	120
HCSS-19.1-29	SS	19.1	0.750	177.8	7	760	50	120
HCSS-19.1-30	SS	19.1	0.750	203.2	8	220	12	120
HCSS-19.1-31	SS	19.1	0.750	203.2	8	500	27	120
HCSS-19.1-32	SS	19.1	0.750	254.0	10	1100	45	240
HCSS-19.1-33	SS	19.1	0.750	304.8	12	550	20	120