

4

3

2

1

ISOMETRIC VIEW  
FOR REF. ONLY

BCE EPOXY

O-RING GROOVE

FLEXIBLE FIBER OPTIC  
CABLE

304L SS CF FLANGE

304 SS SLEEVE

VACUUM SIDE

ATMOSPHERE SIDE

A

D

B

C

ØE

ØF

**NOTES**

- 1. Temperature: Application Specific
- 2. All Dimensions (A to E) are customer specified
- 3. Multiple material and component options available
- 4. BCE Epoxy:
  - a. Outgassing: meets NASA ASTM E595
  - b. Total Mass Loss (TML): <1.0%
  - c. Collected Volatile Condensable Materials: <0.1%
  - d. Dielectric Constant (1 KHz): 3.8

**PROPRIETARY AND CONFIDENTIAL**  
 THE INFORMATION CONTAINED IN THIS  
 DRAWING IS THE SOLE PROPERTY OF  
 BELILOVE CO. ENGINEERS. ANY  
 REPRODUCTION IN PART OR AS A WHOLE  
 WITHOUT THE WRITTEN PERMISSION OF  
 BELILOVE CO. ENGINEERS IS  
 PROHIBITED.

UNLESS OTHERWISE SPECIFIED:		NAME	DATE
DIMENSIONS ARE IN MILLIMETERS		DRAWN	F. SYED 2/15/17
TOLERANCES:		CHECKED	
FRACTIONAL ±		ENG APPR.	
ANGULAR: MACH ±		MFG APPR.	
TWO PLACE DECIMAL ±		Q.A.	
THREE PLACE DECIMAL ±		COMMENTS:	
INTERPRET GEOMETRIC TOLERANCING PER:		THIS DRAWING IS FOR REFERENCE ONLY.	
MATERIAL		FINAL PRODUCT MAY DIFFER.	
FINISH			
DO NOT SCALE DRAWING			



TITLE:		
OPTIC CABLE FEEDTHRU		
SIZE	DWG. NO.	REV
<b>B</b>	BCE10016	<b>A</b>
SCALE: NTS	WEIGHT: N/A	SHEET 1 OF 1

4

3

2

1