















**BCE VACUUM FEEDTHROUGH**

PART NUMBER	FLANGE TYPE	CONDUCTOR	TEMPERATURE	VACUUM SPEC LEAK RATE/TORR	LEAD LENGTH	LEAD GAUGE	VOLT / CURR	WIRES / PINS	STOCK AND PRE-BUILD	VISUAL
STKBCE10571REV1	KF40	SOLID	TC-K	$5 \times 10^{-7}$ cc/sec HE	24" ON EITHER SIDE	20	TC-K	10 Wire	1 DAY	
STKBCE10541REV1	KF40	STRANDED	Application specific	$5 \times 10^{-7}$ cc/sec HE	24" ON EITHER SIDE	26		20 Wire	1 DAY	
STKBCE10569REV1	KF40	STRANDED	Application specific	$5 \times 10^{-7}$ cc/sec HE	24" ON EITHER SIDE	26		45 Wire	1 DAY	
STKBCE10068	CF 1.33	PINS	up to 150°C	$5 \times 10^{-10}$ cc/sec HE - HV $1 \times 10E^{-8}$ Torr	CONNECTORS AVAILABLE		5 AMP	9 PIN	2 DAY	
FL9DK409PIN	KF40-9D	PINS	up to 150°C	$5 \times 10^{-10}$ cc/sec HE - HV $1 \times 10E^{-8}$ Torr	CONNECTORS AVAILABLE		5 AMP PER PIN (Max 20% of Pins)	9 PIN	2 DAY	
FL9DK509PIN	KF50-9D	PINS	up to 150°C	$5 \times 10^{-10}$ cc/sec HE - HV $1 \times 10E^{-8}$ Torr	CONNECTORS AVAILABLE		5 AMP PER PIN (Max 20% of Pins)	9 PIN	2 DAY	
FL15DK5015PIN	KF50-15D	PINS	up to 150°C	$5 \times 10^{-10}$ cc/sec HE - HV $1 \times 10E^{-8}$ Torr	CONNECTORS AVAILABLE		5 AMP PER PIN (Max 20% of Pins)	15 PIN	2 DAY	
FL9D2K5018PIN	KF50-9D2	PINS	up to 150°C	$5 \times 10^{-10}$ cc/sec HE - HV $1 \times 10E^{-8}$ Torr	CONNECTORS AVAILABLE		5 AMP PER PIN (Max 20% of Pins)	18 PIN	2 DAY	
FL9D15DK5024PIN	KF50-9D-15D	PINS	up to 150°C	$5 \times 10^{-10}$ cc/sec HE - HV $1 \times 10E^{-8}$ Torr	CONNECTORS AVAILABLE		5 AMP PER PIN (Max 20% of Pins)	24 PIN	2 DAY	
FL15DL6315PIN	L63-15D	PINS	up to 150°C	$5 \times 10^{-10}$ cc/sec HE - HV $1 \times 10E^{-8}$ Torr	CONNECTORS AVAILABLE		5 AMP PER PIN (Max 20% of Pins)	15 PIN	2 DAY	
FL25DL6325PIN	L63-25D	PINS	up to 150°C	$5 \times 10^{-10}$ cc/sec HE - HV $1 \times 10E^{-8}$ Torr	CONNECTORS AVAILABLE		5 AMP PER PIN (Max 20% of Pins)	25 PIN	2 DAY	
FL15D2L6330PIN	L63-15D2	PINS	up to 150°C	$5 \times 10^{-10}$ cc/sec HE - HV $1 \times 10E^{-8}$ Torr	CONNECTORS AVAILABLE		5 AMP PER PIN (Max 20% of Pins)	30 PIN	2 DAY	
FL50DL10050PIN	L100-50D	PINS	up to 150°C	$5 \times 10^{-10}$ cc/sec HE - HV $1 \times 10E^{-8}$ Torr	CONNECTORS AVAILABLE		5 AMP PER PIN (Max 20% of Pins)	50 PIN	2 DAY	

FL50D2L100100PI	L100-25D2	PINS	up to 150°C	5 x 10 <sup>-10</sup> cc/sec HE - HV 1 x 10E <sup>-8</sup> Torr	CONNECTORS AVAILABLE		5 AMP PER PIN (Max 20% of Pins)	50 PIN	2 DAY	
-----------------	-----------	------	-------------	--	----------------------	--	---------------------------------------	--------	-------	---